

MB 1200: MB Hydraulic Breakers for carriers from 15 up to 26 t weight

3363 0904 41



[PDF erstellen](#)

[Informationen anfordern](#)

Kontakt

[Kontakt details anzeigen](#)

Direktlinks

[Atlas Copco Print Shop](#)

[Atlas Copco Multimedia Gallery](#)

[Produktinformationen](#)

[Fotos und Videos](#)

Atlas Copco's range of medium-duty hydraulic breakers was developed for a wide variety of applications. The combined gas/oil power principle means they are both powerful and highly flexible with regard to oil flow rate and pressure. Their technically advanced percussion mechanism, e.g. with long piston stroke, reduce unavoidable vibrations far more efficiently than many other makes.

Merkmale und Vorteile

- VibroSilenced Plus system
- ContiLube II
- StartSelect
- AutoControl
- Energy recovery
- Percussion chamber ventilation

Applications

- Demolition
- Foundation work
- Tunneling
- Trenching
- Underwater work
- Boulder size reduction in quarries

Technische Daten

Einheiten: [Metrisch](#) [Imperial](#)

Technische Daten	
Gewichtsklasse	15 - 26 t
Betriebsgewicht **	1200 kg
Ölstrom	100 - 140 l/min
Betriebsdruck	160 - 180 bar
Schlagfrequenz	340 - 680 blows/min
Working tool diameter	120 mm
Arbeitslänge des Werkzeugs	610 mm
Max. hydraulische Eingangsleistung	42 kW
garantierter Schalleistungspegel	117 dB(A)

Produktansichten

